

## Product highlights

- \* Multi-detecting zones technology: 8,16,24 detecting zones, it can be shifted and selected intelligent(more zones update technology can be supported) .
- \* Working frequency: Super range working frequency(0-120),and working environment adaptive function
- \* Sensitivity of detecting zone: Sensitivity of single detecting zone can reach 355 grade(adjustable).
- \* Mobile connect technology: Can be controlled by mobile APP.
- \* Super housing protection technology: IP67 excellent protection(selectivity)
- \* Self-adaption diagnosis system: When turn on, system will detect adaptively hardware working status.



^^.Measure body temperature system



^^.Visual conversational system



^^.Passenger detecting video system



^^. Face recognition system



Fold size: 889x606x484mm  
Volume: 0.33m3



Package size: 948x666x525mm  
N.W: 42KG G.W: 50KG

## Product advantage

- \*Adjustment system: System can adjust detecting standard
- \*Start and stop technology:Red infrared device own automatic start and stop technology
- \*It can adds 100 times lifespan
- \*Sensitivity of each zone can be adjusted ( own adjustment technology)
- \*Detecting zones quantity can be selected by yourself
- \*Sound and light alarm. Alarm tones and time can be arbitrarily adjusted
- \*Enquiry function:System provided actual time information enquiry function
- \*Detecting capacity:Can detect more than one hundred persons in one minute

## Unique Features

1. High and low temperature resistance Working normally from -40°C to 85 (selectivity)
2. waterproof: IP67 New deep sea waterproof technology. Working normally underwater at 0.72m
3. Wireless connection(optional) Products can be connected through wifi,4G data, Bluetooth module into internet, remote controlled and data monitored by mobile APP and computer
4. Super long time power supply(optional) Equip polymer batteries, backup power supply time can be 8、16、24、48、72hours for your choice. System automatic alarm to inform you the low battery.

## Product Details

### Characteristic

Detecting target	Contraband goods, more magnet metals
Vertical outside size	2250x850x500mm
Tunnel Size:	2051x710x500mm(Width customized range 700~1500mm)
Fold size:	889x606x484mm
Package size:	948x666x525mm
Working humidity:	99%,no condensing
Working temperature:	-40C~85C
Power supply method:	Equip polymer batteries, last time can be 816,24,48,72hours and can be selected in optional
Output:	DC 12V/5A 12W
Input:	C 110V~240V/50HZ~60HZ
Weight:	N.W 42KG,G.W 50KG
Operating temperature:	-40C to +85C
Relative Humidity:	99%,non-condensing
IP Grade:	IP67
External Dimension:	2250*850*500mm
Passage Dimension:	2051*710*500mm
Fold Dimension:	889*606*484mm
Packing Dimension:	1000*700*540mm
Net Weight:	33kg
Gross weight:	40kg

### Compliance

International	●ISO9001 ●ISO14001 ●HSMS18001 ●CE ●FCC ●ROHS
National (China)	Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center In accordance with: EN60950, WN50081-1, EN50082-1 Electric safety: EN60950 Anti-interference standard: EN50082-1

### Operating Environment

Operation temperature/Humidity	5C-40C / 0%-90%(non-condensing)
Storage temperature/Humidity	-20C-55C / 0%-98%(non-condensing)
Operation Power	220VAC(±10%) 50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)

## SAFEWAY INSPECTION SYSTEM LIMITED



First Factory: BuildingA, QiFeng Digital Park, BaiNiKeng, PingHu Street, LongGang, Shenzhen, China  
 Second Factory: Building B, ShengLongXing Industrial Park, LongTeng Road, PingDi Street, LongGang, Shenzhen, China  
 Tel: +86 - 755-6195 5772 / Fax: +86 - 755-6195 5788  
 Mobile&Whatsapp: + 86- 136 7021 3490 Skype: sophia.xiong8105  
 Email: sophia@cargovehicleinspection.com  
 Website: www.cargovehicleinspection.com